

UCS, Direct instal Microduct koppeling



Productinformatie

De UCS koppelingen maken het lassen van MicroDuct snel en gemakkelijk.

Duw de MicroDucts eenvoudig in het midden van de koppeling. De koppeling kan 10 keer worden aangesloten en losgekoppeld en behoudt nog steeds de hoge prestatie-eisen voor luchtgeblazen installatiesystemen.



Specificaties

- Materiaal:
 - Behuizing :PC, slagvast
 - Klem :POM, roestvrijstaal
 - O-ring :Nitrilrubber

1. Blowing Pressure: Between temperatures of -10°C and $+60^{\circ}\text{C}$, all connectors size can be used for blowing operations at pressures up to 16bar.
2. Burst Pressure: $> 26\text{bar}$
3. Gas Tightness: Leakage at 16 bar gas pressure: 1ml/minute approx.
Leakage at 0.7bar gas pressure: 0.1ml/minute approx.
4. Water ingress: The connectors shall seal against a 6m head of water.
5. Insertion force: 50N max (5kg)
6. Impact: 1J
7. Retention force: 25N min (3mm m/d) 55N min (5mm m/d) 125N min (7&8mm m/d)
(collect not held in) 125N min (10mm m/d) 125N min (12mm m/d) 155N min (14mm m/d)
180N min (16mm m/d) 200N min (18mm m/d) 300N min (20mm m/d)