



FIST™ Splice Sub-assembly kit with 2 trays, each for holding up to 1 12-strip ribbon fiber, with Heat Shrink type splice holder

- Splice sub-assemblies consists of a wraparound groove plate holding the included splice organizer trays
- Groove plates are designed with slots for routing fiber to and from the organizer trays
- Loop-back facility allowing for single circuit uncut looped fiber storage on the splice tray
- Compliant with most splice types and independent of any optical fiber construction

Product Classification

Regional Availability	EMEA
Product Type	Fiber splice tray
Product Brand	FIST™
Product Series	FIST-SOSA2

General Specifications

Application	For use with BUDI fiber wall boxes For use with FIST fiber splice closures For use with FIST fiber splice panels
Color	Gray
Splice Tray Chip Type	Heat shrink
Splice Tray Construction	R12 (for 1 ribbon 12 strip)
Splice Tray Included, quantity	2
Splices per Tray, note	1 mass splice (12-ribbon) per tray
Splices per Tray, quantity	1
Used UMS Units, quantity	3

Dimensions

Height	12 mm 0.472 in
Width	102 mm 4.016 in
Fiber Storage Length, maximum	2050 mm for 12-ribbon fibers
Fiber Storage Length, minimum	650 mm 25.591 in
Length	152 mm 5.984 in
Splice Protector Length, maximum	45 mm 1.772 in
Splice Protector Length, minimum	35 mm 1.378 in
Splice Protector Diameter, maximum	5 mm 0.197 in

337550-000 | FIST-SOSA2-2R12-S

Environmental Space Indoor | Outdoor

Packaging and Weights

Packaging quantity 1

Packaging Type Bag | Carton

Weight, net 0.1 kg | 0.22 lb

Regulatory Compliance/Certifications

Agency

CHINA-ROHS

REACH-SVHC

ROHS

Classification

Below maximum concentration value

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant



* Footnotes

Used UMS Units, quantity The overall used splice tray height is expressed in UMS units. One UMS unit equals 6 mm.